

PRODUCT INFORMATION

With a unique side wall design offering structural integrity to withstand the compaction of surrounding soil, the UP50 also offers an additional riser to allow for fast transformation of pit height when installers require additional height in the pit.

FEATURES

- Offers both Lockable Plastic Lid (Class A) & Resin Lid (Class B)
- Cable entry holes can be cut in the base to suit the size of the ducting
- Base made from robust UV stabilised LDPE proven to withstand harsh elements and perform for decades
- Risers available for installations that require an increase in the depth of the pit connections. These risers are quick and easy to install by attaching the collar to the appropriate pit by means of stainless steel screws
- Base is recyclable with the GYRO-Cycled program
- Pit dimensions: 710 mm x 455 mm x 635 mm
- Pit riser dimensions: 715 mm x 455 mm x 230 mm
- Lid dimensions: 650 mm x 397 mm



PRODUCT SKU'S

SKU	PRODUCT	DESCRIPTION
205040	UP50 ASSEMBLY - CLASS B	Assembly - Black
205041	UP50 ASSEMBLY - RESIN LID CLASS B	Assembly - Resin Lid
205043	UP50 BASE ONLY - BLACK	Base only - Black
205044	UP50 COLLAR ONLY - BLACK RISER	Riser only - Black
205045	UP50 LID ONLY - CLASS B RESIN LID	Lid only - Resin
205042	UP50 LID ONLY - LOCKABLE BLACK LID	Lid only - Black